



US006443460B2

(12) **United States Patent**
Weiss

(10) **Patent No.:** US 6,443,460 B2
(45) **Date of Patent:** Sep. 3, 2002

ELASTIC SEAL FOR A GUIDE ROLLER

- (75) **Inventor:** Josef Weiss, Gössweinstein (DE)
(73) **Assignee:** Ina Walzlager Schaeffler Ohg, Herzogenaurach (DE)
(*) **Notice:** Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 64 days.

(21) **Appl. No.:** 09/764,815

(22) **Filed:** Jan. 18, 2001

Foreign Application Priority Data

Jan. 18, 2000 (DE) 100 01 681
May 18, 2000 (DE) 100 24 529

- (51) **Int. Cl.⁷** F16J 15/32
(52) **U.S. Cl.** 277/549; 384/485
(58) **Field of Search** 277/549, 559, 277/562, 566; 384/58, 449, 484, 485

References Cited

U.S. PATENT DOCUMENTS

3,596,533 A * 8/1971 Nightingale
4,605,318 A * 8/1986 Kaiser
4,808,012 A * 2/1989 Otto
5,676,383 A * 10/1997 Chandler

FOREIGN PATENT DOCUMENTS

DE	0035957	1/1965
DE	1264170	5/1968
DE	7230879	1/1973
DE	2240144	4/1973
DE	7321112	9/1973
DE	8428429	9/1986

OTHER PUBLICATIONS

Search Report dated Jul. 27, 2000 from German Patent Office for Priority Application No. 100 01 681.2.

* cited by examiner

Primary Examiner—Robert J. Sandy

Assistant Examiner—Karlana D. Schwing

(74) *Attorney, Agent, or Firm*—Volpe and Koenig, P.C.

ABSTRACT

A guide roller with a sealing element (14) formed in one piece in a T-shape having a first axial sealing portion (15) that is placed securely onto a shoulder of the inner race, a second sealing portion (16) that extends radially outwardly and is located inside a second groove of the outer race (13), and a third sealing portion (17) that extends radially inwardly branching off from the first sealing portion (15) at its inner end is provided so that axial contact between the shoulder and the outer race (10) is prevented by the third sealing portion (17).

7 Claims, 2 Drawing Sheets

